



NuxReader III

Proximity card reader with 125 kHz RFID technology
or 13.56 MHz Mifare



RFID



Proximity card reader with 125 kHz RFID technology
or 13.56 MHz Mifare



NuxReaderIII

Characteritics

- Compatible with 125 kHz cards or Mifare 1K, 4K cards;
- No need to install drivers;
- Compatible with Windows for Card Reader;
- Resin internal electronics (total protection against humidity);
- Green and Red LEDS;
- Card number extraction in decimal or hexadecimal;

Techhical Specifications

Certification	CE Marking
Cards Reader	RFID with reader up to 8 cm
Comunication	Wiegand or RS232
Operation	Connected to a Innux Terminal or a Computer
Dimensions	43mm x 80mm x 14mm.
Power Supply	DC 12V 50~160mA
Temperature	0° ~ 50° C

Compatibility (Wiegand)



All information is subject to change without notice, given the constant evolution of the product. Innux is not responsible for any errors or omissions in this document.

✉ geral@innux.com

🌐 www.innux.com | www.innux.pt

T.: +351 229 812 220 :: T +351 219 618 404

All photographs and images contained in this document are subject to copyright and may not be copied or reproduced.

© Copyright 2020 Innux Technologies, Lda



 **innux®** | it's about **TIME**